Title: Method and apparatus for measuring a magnetic field by
         using a Hall sensor

5   The invention relates to a method and apparatus for measuring a
magnetic field by using a Hall sensor in accordance with the
preamble of claim 1 and the preamble of claim 12, respectively.

        Sensors which make use of the well-known Hall effect have long
been in widespread use, in particular for carrying out measurements
10   on magnetic fields. In addition to the basic application of
measuring the magnetic field strength, these sensors – referred to
below as "Hall sensors" – are also used, for example, to measure the
position, direction and rotational speed. A conceivable example of
the latter application is the measurement of the rotational speed of
15   gearwheels and driveshafts in machines. In addition, the Hall sensor
serves, for example, to measure the change in the magnetic field
strength when machine components consisting of a magnetic material,
such as for example the teeth of a steel gearwheel, pass through the
magnetic field of a permanent magnet. In this respect, it is also
20   well known for the Hall sensors to be used in anti-lock brake
systems (ABS) for vehicles. For many applications, it is essential
for the permanent magnets/magnetic parts used to be as small and
lightweight as possible. However, one significant drawback in this
respect is the fact that Hall sensors according to the current state
25   of the art are relatively unsuitable for the accurate measurement of
weak magnetic fields (with a magnetic field strength of less than
one milli-Tesla). This drawback generally has the effect of
increasing costs. For example, for Hall sensors to be used
effectively in the abovementioned ABS systems, it is necessary to
30   use expensive rare earth magnets in order to create a sufficiently
high magnetic field strength to allow sufficiently accurate
measurements to be carried out with the aid of the sensor. Also,
applications of this nature impose high demands on the linearity and
accuracy of the required electronic amplification and signal-
35   processing features and on the sensor housing, which likewise has
the effect of increasing costs.

        For many applications, it is desirable for Hall plates,
generally together with amplification and signal-processing
electronics, to be integrated in semiconductor material, for example
40   in silicon using the well-known CMOS process. In addition to the

advantage of simple integration of electronic components in silicon,
this also has the disadvantage that the measurement accuracy and
sensitivity of Hall plates according to the current state of the art
are in fact adversely affected by factors which are inherent to
5   their integration in silicon semiconductor material.

The traditional principle of carrying out measurements on
magnetic fields using Hall plates, when using Hall plates integrated
in silicon semiconductor material, also has an adverse effect on the
measurement accuracy and sensitivity of the sensor. This is because
10   in this traditional measurement principle, a current is used as
excitation signal, and the resulting Hall voltage is measured,
forming a representation of the field strength of the magnetic field
in which the sensor is situated. One significant drawback of this is
that mathematical analysis is able to demonstrate that an integrated
15   Hall sensor has non-linearities which are dependent on an electric
voltage and are very difficult to compensate for when using the
abovementioned principle of current excitation and voltage
detection.

The most important factors inherent in their integration in
20   silicon semiconductor material which have an adverse effect on the
measurement accuracy and sensitivity of Hall plates integrated in
silicon semiconductor material in accordance with the current state
of the art are:

-    offset voltages caused by mechanical stresses in the crystal
25   lattices of the semiconductor materials used via the piezo-
resistance effect;

-    offset voltages caused by the Seebeck effect: temperature
differences create a position-dependent contact potential at the
transition between semiconductor material and metal terminals at
30   different locations on the Hall plate;

-    offset voltages caused by local geometric inaccuracies in the
semiconductor material, formed during the integration process (for
example alignment errors for the terminals, etching variations);

-    offset voltages resulting from accumulated charge at the
35   transition between silicon and silicon oxide;

-    offset and non-linearities of electronic features for, for
example, amplifying and processing output signals from Hall plates,
the said circuits likewise being adversely affected by the
abovementioned factors if they are integrated in semiconductor

material, whether or not on the same substrate as the associated
Hall plates themselves.

Offset voltages in Hall sensors may be greater by a factor of
1000 than the Hall voltages which are ultimately to be measured. In
5   the past, therefore, various methods have been developed attempting
to compensate for the various offset voltages and other
disadvantageous factors in order to increase the measurement
accuracy and sensitivity of Hall sensors.

In a first approximation, a Hall plate can be modelled as a
10 balanced resistance bridge (Wheatstone bridge). The abovementioned
stresses in the crystal lattice of the semiconductor materials used
changes the level of certain resistances in the bridge, resulting in
the formation of an offset voltage which may be of the order of
magnitude of a few tens of milli-Tesla. In addition, the
15 abovementioned Seebeck effect is responsible for a static (current-
and voltage-independent) offset voltage of the order of magnitude of
a few milli-Tesla. This offset voltage is added to the output (Hall)
voltage of the Hall plate. The Hall plate then delivers an output
voltage where no magnetic field is present. The magnetic field
20 strength which would have to be measured with an "ideal" Hall plate
in order to generate a Hall voltage of the same order of magnitude
as this offset voltage may easily amount to several tens of milli-
Tesla.

By mathematical analysis, it is possible to demonstrate that
25 the abovementioned static offset resulting from the Seebeck effect
can be compensated by carrying out measurements in pairs, with the
direction of the excitation current being reversed for the second
sub-measurement in each case and the difference in the Hall voltage
resulting from the two sub-measurements then being determined.
30 Mathematical analysis can also be used to demonstrate that the
abovementioned offset resulting from stresses can be compensated for
by carrying out measurements using two Hall plates, with the second
Hall plate rotated through 90° with respect to the first. The
difference in the output (Hall) voltages from the two Hall plates is
35 in each case determined. US patent 5,241,270 uses this method in
modified form, with two Hall plates employed simultaneously, so that
the two measurements mentioned above can be carried out
simultaneously, rather than in succession.

Numerous known methods which attempt to compensate for the
offset resulting from stresses are based on a configuration also
known as an "orthogonally switched Hall plate", since the current
directions of the excitation currents are perpendicular to one

5   another in the two sub-measurements. Most Hall sensors according to
the current state of the art comprise a square Hall plate with
electrical terminals at the corners. In the case of the
abovementioned offset compensation method using orthogonally
switched Hall plates, the measurements are in most cases carried out

10   in pairs, in which case in the first sub-measurement an excitation
current is passed through the Hall plate between two opposite
terminals, and the resulting Hall voltage is measured across the two
other, opposite terminals. Instead of reversing the direction of the
excitation current as described above, for the second sub-

15   measurement the pairs of terminals for the excitation current and
the Hall voltage are swapped over, so that the direction of the
excitation current is now rotated through 90° with respect to the
direction in the first sub-measurement. The polarity of the Hall
voltage which is measured during the second sub-measurement is then

20   inverted, and this voltage is added to the measured Hall voltage
from the first sub-measurement. Inter alia, patent documents
US 5,406,202, US 5,844,427, EP 1 010 987 A2 and EP 1 130 360 A2
describe Hall sensors in which offset compensation methods of this
type with orthogonally switched Hall plates are used. This method

25   can only provide complete offset compensation if the Hall plates
used were to have a completely linear behaviour in functional
respects. On account of their design, however, Hall plates formed in
semiconductor material are inherently nonlinear. It can be
demonstrated that the most important nonlinearities in Hall plates

30   are dependent on an electric voltage. However, since the offset
compensation methods described above use current excitation and
voltage detection, it is impossible to completely compensate for
nonlinear offset terms. Moreover, according to the method described
of orthogonal switching of Hall plates, the direction of the

35   excitation current cannot be completely (180°) reversed, but rather
can only be turned through 90°, and consequently the offset
resulting from the Seebeck effect is not compensated for, with the
result that a significant offset term remains present. The
literature has disclosed offset compensation methods which make use

of the abovementioned orthogonal switching, but through 360° rather than through 90°. Hall sensors in which this method is used are known in the literature as spinning current Hall sensors. The Hall plates used in this case are generally provided with eight terminals

5 and have a symmetry which is such that in each case a straight connecting line between two opposite terminals is orthogonal (perpendicular) with respect to a straight connecting line between two other terminals. In this case, during eight sub-measurements, in each case a fixed excitation current passes between two opposite

10 terminals, and the associated Hall voltage is measured between the two terminals whose straight connecting line is orthogonal with respect to the straight connecting line between the two terminals mentioned first. The resulting Hall sensor is produced by the German Fraunhofer IIS. The relatively large number of terminals of the Hall

15 plate in this sensor, however, is responsible for an undesirable reduction in the sensitivity of the sensor with respect to Hall plates having a smaller number of terminals. In this case too, current excitation and voltage detection are used, and consequently nonlinear offset terms are not fully compensated for.

20   US patent 5,621,319 describes a method for compensating for the offset resulting from mechanical crystal stresses in integrated Hall sensors. Use is made of the above-described spinning method with orthogonal switching of the Hall plate. In addition, use is made of voltage excitation rather than current excitation. However, the

25 drawback is that this voltage excitation is combined with voltage detection, and consequently the offset resulting from stresses is not in fact compensated for, on account of the directional-dependent nature of electrical properties of the semiconductor material (anisotropy).

30   In many patent documents, such as the abovementioned US 5,406,202 and US 5,844,427, which describe methods for compensating for the offset resulting from crystal stresses in integrated Hall sensors, it is attempted to achieve initial offset compensation by parallel-connection of a plurality of Hall plates

35 which are rotated through a defined angle with respect to one another. In most cases, this involves two Hall plates which are rotated through an angle of 90° with respect to one another. It can be demonstrated by mathematical means that this approach can only function optimally if four Hall plates are connected in parallel, of

which the second, third and fourth plates are respectively rotated through 90, 180 and 270° with respect to the first plate, and if voltage excitation and current detection are also used. Document EP 1 206 707 B1 does indeed use a configuration with four Hall

5   plates, but these plates are only rotated through in each case 45° rather than 90°. In functional terms, the four Hall plates in this case in reality form a single spinning current Hall plate with eight terminals, as described above, with the associated drawbacks as likewise described above.

10   A further significant source of offset in Hall sensors is the offset and nonlinearity of electronic features for, for example, amplifying and processing output signals from Hall plates. The fact that these electronic features are often integrated with the Hall plates in the same semiconductor substrate offers possibilities for,

15   for example, combining compensation for the offset of an integrated amplifier with compensation for the offset of a Hall plate resulting from the Seebeck effect. US 6,154,027 describes a method in which the output signal of a spinning current Hall plate is firstly pre-amplified before being demodulated. However, this involves spinning

20   through 90° in two stages rather than spinning through 360° in four stages. Consequently, the offset resulting from the SEEBECK effect is not compensated for.

       The offset resulting from mechanical crystal stresses in the semiconductor material of a Hall sensor varies for different crystal

25   directions. Nevertheless, the relevant literature in this field provides scarcely any information about the optimum orientation of a Hall plate in semiconductor material. Research carried out by the Applicant has demonstrated that the sensitivity of a Hall plate to stress can be reduced by a factor of 10 by selecting the appropriate

30   orientation.

       To summarize, on the basis of what has been stated above, it can be concluded that hitherto it has not been possible to solve the problems inherent to the current state of the art in this field in order to sufficiently compensate for the effect of factors which

35   have a negative influence on the measurement accuracy and sensitivity of integrated Hall sensors.

       It is an object of the present invention to eliminate the abovementioned drawbacks.

According to the invention, this object is achieved by the
provision of a method according to claim 1.

One significant advantage obtained as a result is that for each
Hall plate used, there are no nonlinearities dependent on an

5   electric voltage. Even for the above-described method for initial
compensation for the offset resulting from crystal stresses in
integrated Hall sensors by parallel connection of a plurality of
Hall plates rotated with respect to one another to function
optimally, it is more advantageous to use the voltage

10   excitation/current detection combination.

Furthermore, according to the method of the invention, to
perform measurements on magnetic fields using a Hall sensor, it is
advantageously possible to use Hall plates whose largest plane has
two pairs of terminals (A1, A2) and (B1, B2), with the terminals of

15   each pair of terminals being placed at opposite positions in the
said plane of the plate, and with the abovementioned plane of the
plate being shaped in such a manner that the abovementioned plane of
the plate is mirror-symmetrical with respect to the straight
connecting line between the two terminals of a pair of terminals.

20   Measurements using Hall plates according to the invention of this
type are then characterized by the fact that an excitation voltage
$V_{ex}(X+,Y-)$ is applied to a pair of terminals (X, Y), with (X, Y)$\in$
{(A1, A2), (B1, B2)}, and the detection current I_{det} (X → Y) which
flows through the Hall plate between the terminals of the other pair

25   of terminals being measured with short-circuited terminals of the
latter pair of terminals, the measurement being carried out in four
stages

$\{V_{ex}(A1, A2), I_{det} (B1 → B2)\}$

30     $\{V_{ex}(B1, B2), I_{det} (A2 → A1)\}$

$\{V_{ex}(A2, A1), I_{det} (B2 → B1)\}$

$\{V_{ex}(B2, B1), I_{det} (A1 → A2)\}$

which can be run through in any desired order, during which period

35   the type and signal form of the excitation voltage remain constant,
after which a representation of the measured variable is determined
via electronic processing from the four measured values for the
detection signal $I_{det}(X → Y)$. However, the nature and/or signal form
of the excitation voltage can be altered between the abovementioned

measurements comprising four stages. In many cases, the
abovementioned "measured variable" will be the magnetic field
strength.

This is therefore a spinning voltage method, with the spinning
5   taking place through 360°, in stages of 90°. As described above, it
is in this way possible to effect optimum compensation for the
offset resulting from the Seebeck effect. It is also possible to use
Hall plates with just four terminals, which is of benefit to the
sensitivity of the Hall sensor.

10   Furthermore, according to the method of the invention, to carry
out measurements on magnetic fields using a Hall sensor, it is
advantageous for the abovementioned determination of a
representation of the measured variable via electronic processing of
the abovementioned four measured values for the detection signal
15   $I_{det}(X \rightarrow Y)$ only to be allowed to take place after this detection
signal has been amplified.

In this way, when using the above-described spinning voltage
method through 360°, in steps of 90°, it is possible to compensate
for both the offset resulting from the Seebeck effect and the offset
20   of the amplifier in a single step. The said electronic processing of
the measured values for the detection signal could, for example, be
quadrature demodulation. The method according to the invention for
carrying out measurements on magnetic fields using a Hall sensor may
furthermore advantageously be characterized by the fact that the
25   said electronic processing of the said four measured values for the
detection signal $I_{det}(X \rightarrow Y)$ comprises, inter alia, averaging of
these measured values.

According to the method of the invention for carrying out
measurements on magnetic fields using a Hall sensor, it is
30   preferable to use Hall plates which are formed in n-type silicon
semiconductor material.

Hall plates which are formed in p-type silicon have a weaker
Hall effect than n-type plates, with the result that factors causing
offset, such as for example crystal stresses, have in relative terms
35   a greater detrimental influence. p-Type Hall plates are therefore
less suitable for achieving optimum offset compensation.

According to the method of the invention for carrying out
measurements on magnetic fields using a Hall sensor, it is
furthermore advantageous, if the said semiconductor Hall plates are

produced in n-type silicon semiconductor material via a process
which has resulted in the substrate surface coinciding with the
(100) crystal plane of the silicon semiconductor material, to use
Hall plates whose orientation in the crystal plane is such that the
5   straight connecting line between the terminals A1 and A2 of the pair
of terminals (A1, A2) and the straight connecting line between the
terminals B1 and B2 of the pair of terminals (B1, B2) coincides with
or is orthogonal with respect to the [010] or [001] crystal axes or
equivalent crystal directions of the silicon semiconductor material.
10   When using a Hall plate as described above, with four
terminals, and voltage spinning through 360°, in stages of 90°, it
is therefore possible, according to research carried out by the
Applicant, to reduce the offset resulting from mechanical crystal
stresses by a factor of ten. In the case of the abovementioned,
15 known Hall plate with eight terminals and using current spinning, it
is never possible to achieve the ideal orientation of the plate,
since in that case there will always be pairs of terminals whose
straight connecting line neither coincides with nor is orthogonal
with respect to the [010] or [001] crystal axes or equivalent
20 crystal directions of the silicon semiconductor material.
        According to the method of the invention for carrying out
measurements on magnetic fields using a Hall sensor, it is
advantageously possible to use four of the said Hall plates, each
with two pairs of terminals (A1, A2) and (B1, B2), with the second,
25 third and fourth plates respectively rotated through 90°, 180° and
270° with respect to the first plate, and the four plates being
parallel-connected as a result of in each case the corresponding
terminals of the four plates being connected to one another.
        Therefore, in combination with voltage excitation and current
30 detection, it is possible to achieve a reduction in the offset
resulting from mechanical crystal stresses and the offset resulting
from the Seebeck effect.
        According to the method of the invention for carrying out
measurements on magnetic fields using a Hall sensor, it is
35 furthermore advantageous to use a Hall sensor having the said four
parallel-connected Hall plates which comprises a silicon chip in
which the four Hall plates are all integrated in the same silicon
substrate.

This allows optimum compensation for the offset resulting from crystal stresses and the offset resulting from the Seebeck effect. If, moreover, the optimum orientation of the first Hall plate with respect to the crystal axes has been determined, this is

5   automatically also optimal for the other three plates, despite their rotated positions.

According to the method of the invention for carrying out measurements on magnetic fields using a Hall sensor, it is preferable to use Hall plates which comprise a layer of n-type

10   silicon located between an underlying substrate of p-type silicon and a top layer of p-type silicon.

This structure, which is known as a pinched structure, generates less flicker noise. Also, pinching results in the formation of broader depletion regions in the layer of n-type

15   silicon, and consequently the Hall plate effectively becomes thinner, which increases the sensitivity of the plate. One drawback is that a Hall plate with pinching is less linear than a plate which is not pinched. The use of voltage excitation and current detection makes it possible to compensate for the nonlinearity which is

20   dependent on an electric voltage.

According to the method of the invention for carrying out measurements on magnetic fields using a Hall sensor, it is advantageously possible for the output signal from the abovementioned Hall plate(s) to be passed through a delay line with

25   a structure which is such that, after they have been summed and averaged, the measured values are delivered with the same frequency as the frequency with which the said four measurement stages $\{V_{ex}(X+, Y-), I_{det}(X \rightarrow Y)\}$ are passed through.

One drawback of spinning methods in general is the fact that a

30   plurality of sub-measurements have to be carried out for each representation of the measured variable. This drawback is compensated for by the use of a delay line as described above. This method is also known as staggered processing. A combination of this with, for example, quadrature demodulation allows both the offset

35   and the Hall signal to be estimated. The estimates for the offset can then be used to optimize the dynamic range of the Hall sensor.

The abovementioned object is also achieved, according to the invention, by the provision of an apparatus according to claim 12.

In addition to the evident advantages of the integration of a
plurality of electronic features, another important advantage is the
fact that the variation in, for example, material parameters and
temperature between separate integrated circuits, known as inter-
5   chip variation, is generally greater than the variation between
circuits which are integrated in the same silicon substrate, known
as intra-chip variation. Therefore, the latter variant offers better
options for offset compensation.

The invention will be explained in more detail in the following
10   text on the basis of exemplary embodiments of apparatuses according
to the invention, in which the method according to the invention is
implemented, which are diagrammatically depicted in the drawings. In
this context, it should be noted that the variant embodiments
illustrated are selected purely by way of illustration but do not in
15   any way restrict the scope of application of the invention.

In the drawings:

Fig. 1 diagrammatically depicts a variant embodiment of a Hall
sensor according to the invention in which the method according to
the invention is implemented;

20   Figs. 2 to 5 diagrammatically depict currents which occur in
Hall plates of the sensor shown in Fig. 1 in various phases of
operation of the latter;

Fig. 6 diagrammatically depicts another variant embodiment of
the wiring around and between the Hall plates shown in Fig. 1 and
25   their terminals with the wiring;

Figs. 7 to 10 diagrammatically depict currents which occur in
the Hall plates when using the wiring and terminals thereof as shown
in Fig. 6; and

Fig. 11 diagrammatically depicts a preferred variant of the
30   wiring around and between the Hall plates shown in Fig. 1 and their
terminals with the wiring.

In the following description of a Hall sensor with reference to
Fig. 1, it is assumed that the Hall plates, electronic features and
wiring illustrated are all integrated in the same silicon substrate
35   and form part of the same silicon chip. Furthermore, it is assumed
that use is made of n-type Hall plates, that the integrated circuit
has a pinched structure and that the substrate surface coincides
with the (100) crystal plane of the silicon semiconductor material
used.

The variant embodiment of a Hall sensor according to the invention comprises a combined Hall plate composed of four sub-plates 101 to 104. Each sub-plate has a group of two pairs ((A1, A2), (B1, B2)) of terminals (A1, A2, B1, B2). The terminals of each

5   pair are arranged at opposite corners of the sub-plate, in such a manner that connecting lines between the terminals of the respective pairs are perpendicular to one another. The groups of pairs of terminals of adjacent plates are rotated through 90° with respect to the perpendicular to the plates.

10   As shown in Fig. 1, the sub-plates 101 to 104 are arranged in a square formation. The direction in which groups of pairs of terminals of adjacent plates have been rotated through an angle of 90°, referred to here as the group orientation, is identical to the direction of the order in which the sub-plates in question are

15   viewed, referred to below as the sub-plate orientation.

Corresponding terminals of the four sub-plates are electrically connected to one another, so that the four sub-plates are in fact connected in parallel. As can be seen from Fig. 1, for all the sub-plates it is the case that the straight connecting line between the

20   terminals belonging to a pair of terminals is parallel to or orthogonal with respect to the [010] or [001] crystal axes, which are also indicated in the figure.

The four parallel-connected terminals of the combined Hall plate are now connected to the four outputs of switching means 106

25   and 107 and to the two inputs of switching means 108 and 109, as shown in Figure 1. The said switching means 106, 107, 108 and 109, which in technical terms can be realized in numerous known ways and using conventional components, receive a clock signal from oscillator 111 and have four switching states (1 to 4); in each

30   switching state, an input of the switching means is connected to an output of the same switching means. In the figure, the arrows in the switching means denote which input is connected to which output for each switching state. For example, in switching state 1, the input of switching means 106 is connected to the terminals A1 of the

35   combined Hall plate, and in switching states 1 and 2, the terminals B1 of the combined Hall plate are connected by switching means 108 to the output of the latter switching means. Switching states 1 to 4 are passed through cyclically, as triggered by a clock signal generated by oscillator 111.

The inputs of switching means 106 and 107 are connected to voltage source 105, which has an impedance that is negligible for use of the sensor, preferably zero, and delivers a voltage which is suitable for use as excitation voltage for the Hall plates. The

5   switching means 106 and 107 and the parallel connection of the sub-plates 101, 102, 103 and 104 of the combined Hall plates now ensure that, for each cycle of four switching states, the said excitation voltage from voltage source 105 is applied twice to each of the two pairs of terminals of the sub-plates, once with an inverted sign.

10   Each time per switching state that the excitation voltage is applied to four parallel-connected pairs of terminals of the four sub-plates, the switching means 108 and 109 ensure that the total of the (Hall) currents which pass through the other four parallel-connected pairs of terminals of each sub-plate are read (detected) and fed to

15   two differential inputs of an amplification means 110. The latter may, for example, be a current amplifier. The impedance of the amplifier means 110 between the differential inputs is negligible and preferably zero. Each of the differential inputs of the amplifier means 110 has a high, preferably infinite impedance to

20   earth (ground). This way, the currents which then pass through the Hall plates and the differential inputs of the amplifier means 110 are approximately short-circuit currents and form a representation of the magnetic field strength measured by the Hall sensor. Following the amplification means 110, the sign of two of the four

25   measured values which are supplied during a cycle of four switching states is inverted by the two switching means 112 and 113. These switching means, which in technical terms can be realized in a wide range of known ways and using conventional components, receive a clock signal from oscillator 111 and, like the switching means 106

30   to 108, have four switching states (1 to 4), as indicated in the figure.

The variant embodiment of the apparatus according to the invention described here is in fact a spinning voltage Hall sensor with four terminals. The currents which are read can be processed

35   further in both analogue and digital form, depending on the requirements of the specific application. Analogue-digital converters and other auxiliary electronic means are of no relevance to the present description and are therefore not depicted in the figure.

On account of the fact that the "spinning" comprises four
stages, coinciding with the four abovementioned switching states,
the Hall sensor described here could supply an output value after
each cycle of four stages. To obtain a representative measured value

5   more quickly, it is possible to use staggered processing. In this
case, the outputs of the switching means 112 and 113 are connected
to a delay line comprising three sections 114, 115 and 116. Under
the control of the oscillator 111, during each switching state an
output signal from the switching devices 112 and 113 is fed to the

10   delay line. The outputs of the said switching devices 112 and 113
and the outputs of each of the three sections 114, 115 and 116 of
the delay line are connected to an adding means 117, which under the
control of oscillator 111 adds up the output signals of the
switching features 112 and 113, and the output signals from the

15   sections 114, 115 and 116 of the delay line, during each switching
state. The adding means 117 supplies, at an output 118 of the Hall
sensor, an output signal which represents an average measured value
of which the average moves with the frequency of the oscillator 111.

       Figs. 2 to 5 show, without reference numerals and letters for

20   the sake of clarity, the four Hall plates 101 to 104 from Fig. 1 for
the respective four switching states described. In Figs. 2-5, arrows
show the currents which pass through the plates 101-104 and, at the
same time, through the voltage source 105 during the four
abovementioned switching states of the switching means 106 and 107.

25   It can be seen from Figs. 3 and 5 that the currents shown
together correspond to a current through a loop comprising a coil
with a single turn. Since the plates 101-104 are of limited size,
the integral of the magnetic flux in the plane of the loop will not
be equal to zero irrespective of the direction of the current. As a

30   result, in the situations shown in Figs. 3 and 5, this current
generates a residual magnetic field which has an adverse effect on
the measurement of an external magnetic field.

       Fig. 6 shows the Hall plates 101-104, with the terminals A1,
A2, B1, B2 arranged in such a manner, and with associated wiring

35   which is such, that the group orientation of the terminals A1, A2,
B1, B2 is opposite to the sub-plate orientation. As a result, the
terminals of the sub-plates in the centre of the combined plate are
alternately connected to two different terminals of the switching
means 106 and 107 for the same pair of terminals (A1, A2 in Fig. 6).

Figs. 7 to 10, like Figs. 2 to 5, use arrows to show the direction of the currents which pass through the plates 101-104 and, at the same time, through the voltage source 105 in the four switching states of the switching means 106 and 107.

5   The situations shown in Figs. 7 and 9 correspond to the situations shown in Figs. 2 and 4.

The situations shown in Figs. 8 and 10 appear to correspond to the situations shown in Figs. 3 and 5. However, in the situations shown in Figs. 8 and 10, the integral of the magnetic flux generated

10   by the currents over the finite surface area of the Hall plates is minimal (zero under ideal conditions and without external magnetic field). As a result, these currents will generate (virtually) no residual magnetic field in the sub-plates, and consequently they have no adverse effect on the measurement of an external magnetic

15   field. For this reason, the arrangement of the sub-plates shown in Fig. 6 is preferred.

The currents in the various sections of the wiring between and around the sub-plates 101-104 also appear to have the ability to cause a residual magnetic field in the sub-plates, which has an

20   adverse effect on the measurement of an external magnetic field, as a function of the arrangement of the wiring. Fig. 11 shows an arrangement of the wiring which generates a minimal residual magnetic field. Therefore, the arrangement of the wiring shown in Fig. 11 is preferred. The same also applies to other arrangements of

25   the wiring to obtain a similar result.

It should be noted that it will be clear to a person skilled in the art, on reading the description and the claims, that various alternative embodiments are possible within the scope of the appended claims. For example, it is possible for the plurality of

30   Hall plates to be arranged in different locations and with different orientations with respect to one another from those described here and shown in the figures. Within the scope of the claims, it is possible for a Hall plate to be arranged even with its main plane perpendicular to a main plane of a substrate, and for its terminals

35   to be arranged at a main plane of the substrate along a single edge of the Hall plate, in which case terminals belonging to one pair of terminals alternate with terminals belonging to the other pair of terminals.